



SIERRA API

Example Body: Items

```
## POST /v6/items/
##
## Create item record with fixed- and variable-length data.
## Replace item type, agency, location, item code 2, status,
## item message and opac message with local information. Attach
## item to bib record b1259533.
##

{
    "copyNo": 1,
    "itemType": 0,
    "price": 2000,
    "agency": 2,
    "location": "epaf",
    "barcodes": [
        "84548856"
    ],
    "itemCode1": 0,
    "itemCode2": "-",
    "status": "-",
    "stickyStatus": "-",
    "itemMessage": "-",
    "oPACMessage": "-",
    "messages": [
        "This is a message"
    ],
    "internalNotes": [
        "This is a note"
    ],
    "bibIds": [
        1259533
    ],
    "varFields": [
        {
            "fieldTag": "c",
            "marcTag": "099",
            "value": "TEST RECORD"
        }
    ]
}
```

```

    "subfields": [
        {
            "tag": "a",
            "content": "FIC MOXON"
        }
    ]
}
]

}

## POST /v6/items/query
##
## Search item records with patron number greater than 0,
## due date earlier than 7/19/2021 (can replace with today's
## date) and item location code beginning with 'iu'.
##

{
    "queries": [
        {
            "target": {
                "record": {
                    "type": "item"
                },
                "id": 66
            },
            "expr": [
                {
                    "op": "greater_than",
                    "operands": [
                        "p0000000"
                    ]
                }
            ]
        },
        "and",
        {
            "target": {
                "record": {
                    "type": "item"
                },

```

```

    "id": 65
},
"expr": [
{
  "op": "less_than",
  "operands": [
    "07-19-2021"
  ]
}
],
},
"and",
{
  "target": {
    "record": {
      "type": "item"
    },
    "id": 79
  },
  "expr": [
    {
      "op": "starts_with",
      "operands": [
        "iu"
      ]
    }
  ]
}
]
}

## PUT /v6/items/{id}
##
## Update fixed- and variable-length data in an item record. Replace
## item type, agency, location, item code 2, status, item message and
## opac message with local information. Note: Item record number is
## placed in the URI.
##
{

```

```
"copyNo": 2,  
"itemType": 14,  
"inventoryDate": "2021-08-16",  
"price": 699,  
"agency": 3,  
"location": "iuav",  
"barcodes": [  
    "30102000133249"  
,  
    "itemCode1": 100,  
    "itemCode2": "-",  
    "status": "o",  
    "itemMessage": "a",  
    "oPACMessage": "c",  
    "messages": [  
        "Send item to Brenda for additional processing when returned."  
,  
        "callNumbers": [  
            "NK1510 .B53 1977"  
        ]  
    ]  
}
```

This publication is supplied for the exclusive use of customers of Innovative Interfaces with the understanding that it shall not be shown or distributed to anyone outside of the customer's organization without the prior written permission of Innovative Interfaces. This publication may be copied only if the copies are for the exclusive use of staff members of libraries that have purchased the Innovative system.

© 2021, Innovative Interfaces, Inc.